Semaphores — OS Support for Mutual Exclusion (Review)

- Even with semaphores, some synchronization errors can occur:

Honest Mistake	Careless Mistake

milk->V( );
if (noMilk)
  buy milk;
milk->P( );
	milk->P( );
	if (noMilk)
	  buy milk;
	milk->P( );

  - Other variations possible

- Solution — new language constructs
  - (Conditional) Critical region
    - **region** v **when** B **do** S;
    - Variable v is a shared variable that can only be accessed inside the critical region
    - Boolean expression B governs access
    - Statement S (critical region) is executed only if B is true; otherwise it blocks until B does become true
  - Monitor

From Semaphores to Locks and Condition Variables

- A semaphore serves two purposes:
  - Mutual exclusion — protect shared data
    - mutex in Coke machine
    - milk in Too Much Milk
    - Always a binary semaphore
  - Synchronization — temporally coordinate events (one thread waits for something, other thread signals when it's available)
    - fullSlot and emptySlot in Coke machine
    - Either a binary or counting semaphore
- Idea — two separate constructs:
  - *Locks* — provide mutually exclusion
  - *Condition variables* — provide synchronization
  - Like semaphores, locks and condition variables are language-independent, and are available in many programming environments

Locks

- *Locks* provide mutually exclusive access to shared data:
  - A lock can be "locked" or "unlocked" (sometimes called "busy" and "free")
- Operations on locks (Nachos syntax):
  - Lock(*name) — create a new (initially unlocked) Lock with the specified name
  - Lock::Acquire( ) — wait (block) until the lock is unlocked; then lock it
  - Lock::Release( ) — unlock the lock; then wake up (signal) any threads waiting on it in Lock::Acquire( )
- Can be implemented:
  - Trivially by binary semaphores (create a private lock semaphore, use P and V)
  - By lower-level constructs, much like semaphores are implemented

Locks (cont.)

- Conventions:
  - Before accessing shared data, call Lock::Acquire( ) on a specific lock
    - Complain (via ASSERT) if a thread tries to Acquire a lock it already has
  - After accessing shared data, call Lock:: Release( ) on that same lock
    - Complain if a thread besides the one that Acquired a lock tries to Release it
- Example of using locks for mutual exclusion (here, "milk" is a lock):

Thread A	Thread B

milk->Acquire( );
if (noMilk)
  buy milk;
milk->Release( );
	milk->Acquire( );
	if (noMilk)
	  buy milk;
	milk->Release( );

  - The test in threads/threadtest.cc should work exactly the same if locks are used instead of semaphores

Locks vs. Condition Variables

- Consider the following code:

```
Queue::Add( ) {
    lock->Acquire( );
    add item
    lock->Release( );
}

Queue::Remove( ) {
    lock->Acquire( );
    if item on queue
        remove item
    lock->Release( );
    return item;
}
```

  - Queue::Remove will only return an item if there's already one in the queue

- If the queue is empty, it might be more desirable for Queue::Remove to wait until there is something to remove
  - Can't just go to sleep — if it sleeps while holding the lock, no other thread can access the shared queue, add an item to it, and wake up the sleeping thread
  - Solution: **condition variables** will let a thread sleep <u>inside</u> a critical section, by releasing the lock while the thread sleeps

Condition Variables

- *Condition variables* coordinate events
- Operations on condition variables (Nachos syntax):
  - Condition(*name) — create a new instance of class Condition (a condition variable) with the specified name
    - After creating a new condition, the <u>programmer</u> must call Lock::Lock( ) to create a lock that will be associated with that condition variable
  - Condition::Wait(conditionLock) — release the lock and wait (sleep); when the thread wakes up, immediately try to re-acquire the lock; return when it has the lock
  - Condition::Signal(conditionLock) — if threads are waiting on the lock, wake up <u>one</u> of those threads and put it on the ready list; otherwise do nothing

Condition Variables (cont.)

- Operations (cont.):
  - Condition::Broadcast(conditionLock) — if threads are waiting on the lock, wake up <u>all</u> of those threads and put them on the ready list; otherwise do nothing
- **Important**: a thread **<u>must</u>** hold the lock before calling Wait, Signal, or Broadcast
- Can be implemented:
  - Carefully by higher-level constructs (create and queue threads, sleep and wake up threads as appropriate)
  - Carefully by binary semaphores (create and queue semaphores as appropriate, use P and V to synchronize)
    - This sounds possible, but actually it does not work — details on why next time
  - Carefully by lower-level constructs, much like semaphores are implemented

Using Locks and Condition Variables

- Associated with a data structure is both a lock and a condition variable
  - Before the program performs an operation on the data structure, it acquires the lock
  - If it needs to wait until another operation puts the data structure into an appropriate state, it uses the condition variable to wait
- Unbounded-buffer producer-consumer:

```
Lock *lk;
Condition *c;
int avail = 0;

/* producer */
while (1) {
    lk->Acquire( );
    produce next item
    avail++;
    c->Signal(lk)
    lk->Release( );
}

/* consumer */
while (1) {
    lk-> Acquire( );
    if (avail==0)
        c->Wait(lk);
    consume next item
    avail--;
    lk->Release( );
}
```