

Name: _____

- c. A round-robin CPU scheduler may perform a context switch 100-1000 times a second. What is a context switch, and what does the operating system have to do during one? (4 points)

- d. Following up on part (c.) above, why is a context switch performed so often? (2 points)

- e. Following up on part (c.) above, why isn't a context switch performed more often? (2 points)

4. Consider this algorithm for mutual exclusion. (7 points)

```
Process 1 {  
  while true {  
    while (turn == 1)  
      ; /* do nothing */  
    critical section  
    turn = 2;  
    other non-critical code  
  }  
}
```

```
Process 2 {  
  while true {  
    while (turn == 2)  
      ; /* do nothing */  
    critical section  
    turn = 1;  
    other non-critical code  
  }  
}
```

- a. Does it satisfy mutual exclusion? Explain. (2 points)

Name: _____

b. Does it prevent deadlock? Explain. (2 points)

c. What problems does this solution have? (3 points)

5. Consider this implementation of semaphores. (9 points)

<code>wait(s):</code>	<code>signal(s):</code>
<code> <i>disable interrupts</i></code>	<code> <i>disable interrupts</i></code>
<code> while (s <= 0)</code>	<code> s = s + 1;</code>
<code> ; /* do nothing */</code>	
<code> s = s - 1;</code>	
<code> <i>enable interrupts</i></code>	<code> <i>enable interrupts</i></code>

a. What is the purpose of disabling the interrupts? (3 points)

b. What problems are there with disabling the interrupts? (3 points)

Name: _____

9. Many concepts and algorithms are applicable to more than one problem. For example, the first-fit and best-fit algorithms can be used to place objects into holes. Describe at least two of the three situations discussed in class for which these algorithms can be used in an operating system and how they might be used in each situation. For extra credit, do this for all three situations. (6 points)

10. Demand paging is the most common method of memory management used in modern operating systems. (12 points)
 - a. Draw a diagram and explain how virtual addresses are converted into physical addresses using paging. (5 points)

 - b. What kind of fragmentation can occur in paging? Explain. (3 points)

 - c. What is a page fault, and what must the operating system do when this happens? (4 points)

Name: _____

11. Fill out the following table, listing those items that are stored in each data structure in UNIX. For extra credit, do the same thing for Nachos. (12 points)

Item	UNIX	Nachos (extra credit)
Partition (4 points)		
File descriptor (5 points)		
Directory (3 points)		